# G-Chem<sup>™</sup> Beam Pump



The G-Chem Beam Pump provides reliable and robust means of injecting chemicals by operating with a pumpjack. The G-Chem is a positive displacement plunger type pump powered by a direct connection with a cable or rod to the pumpjack's walking beam.

The G-Chem Beam Pump offering includes:

- Three preset stroke positions
- Unique actuator design with a hex shape connection allowing for additional handle positions for more accurate dosing
- · Stainless steel heads for withstanding the harshest applications
- Common repair parts are shared with the G-Chem electric pump, such as packings, plungers, check valves and fluid heads

#### **Features**

- Maximum flow rates up to 20 gallons per day
- Stroke adjustment range from 1/2" to 1"
- Maximum discharge pressure of 2,500 PSI
- Graco's Chromex<sup>™</sup> coated plunger rods
- Graco's poppet style check valves
- FKM, HNBR and TFE/P seals
- Interchangeable fluid heads with G-Chem electric series pumps

## **Technical Data**

18 Stokes/ min	Plunger Size		Gallon/day		Plunger Size		Gallon/day	
	1/4"	min	1.0	10 Stokes/ min	1/4"	min	0.5	
		max	4.5			max	2.5	
	3/8"	min	2.5		3/8"	min	1.3	
		max	10.5			max	5.7	
	1/2"	min	4.4		1/2"	min	2.3	
		max	20.0			max	10.0	

15 Stokes/ min	Plunger Size		Gallon/day		Plunger Size		Gallon/o
	1/4"	min	0.8	5 Stokes/ min	1/4"	min	0.3
		max	3.7			max	1.2
	3/8"	min	2.0		3/8"	min	0.7
		max	8.5			max	2.8
	1/2"	min	3.5		1/2"	min	1.2
		max	15.0			max	5.0

## **Ordering Information**

A-Chen

day

G-Chem Beam Pump Part Numbers						
Seals / Plunger Size	1/4"	3/8"	1/2"			
FKM	A23000	A23001	A23002			
HNBR	A23003	A23004	A23005			
TFE/P	A23006	A23007	A23008			



### Call 866-552-1868 today for product information or to request a demonstration.

©2018 Graco Inc. 360062 Rev. A 10/18 Printed in the U.S.A. All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice. All other brand names or marks are used for identification purposes and are trademarks of their respective owners.

#### Zimco Instrumentation Inc.

11141 15 Street NE, Calgary, AB, T3K 0Z5 Canada | Phone: 403-253-8320 | Email: info@zimco.ca | Website: www.zimco.ca